

Solar-Werkstatt Ltd

Power for all - everywhere







Features

System voltage: 12 V_{DC} | Photovoltaics: 30 Wp | Battery: 540 Wh | Incl. 1 water resistant DC-lamp | Weight: 18 kg | Guarantee: 2 Years

SolarBox 45

Robust and powerful 12 Volt DC off-grid photovoltaic system, made in Switzerland. Portability coupled with good performance - ideal for lighting, radio and laptops, in huts, cars or boats.

Advantages:

- Ease of use: Plug and Play, ready for operation after plug in of the photovoltaicmodule
- Robustness: Developed to withstand harsh climatic conditions, solid stackable aluminum design guarantees no damage to internal electronics even under large mechanical loads
- Quality: All connectors protected against water and dust. Inside the SolarBox a fully encapsulated industrial charge controller guarantees the optimum performance of a maintenance-free, sealed solar gel-battery for many years
- Modular: Possibility to extend the system by connecting additional SolarBoxes or photovoltaic-modules in parallel
- Flexibility: Possibility to connect an external DC-AC Inverter
- Mobile

www.solar-werkstatt.ch www.solarbox.ch




Technical Specifications

| SolarBox 45 | |
|--|--|
| System voltage | 12 V _{DC} |
| Battery technology | Maintenance free solar gel battery |
| Battery capacity | 540 Wh 45 Ah C10 12 V |
| Max. PV input | 300 Wp |
| Charge controller | Morningstar (USA) |
| Max load | 20 A _{DC} |
| Protection | Low and high voltage protection |
| Low Voltage disconnect / reconnect | 11.4 / 12.6 V |
| Weight of SolarBox | 18 kg |
| Dimensions of SolarBox | 0.3 x 0.25 x 0.25 m |
| Connectors | 1 x PV-In (polarity protected) 1 x In / Out battery direct (polarity protected) 3 x Out 12 V cigarette lighter connector |
| Extension possibilities | Yes, modules or SolarBoxes |
| Inverter connection | Yes / external |
| Charger connection | Yes / external |
| | |
| Photovoltaic-Module (external) | |
| Photovoltaic-Module (external) PV-Module (Standard) | 30 Wp (monocristallin, aluminum frame) |
| | 30 Wp (monocristallin, aluminum frame) 3.5 kg |
| PV-Module (Standard) | |
| PV-Module (Standard) Weight | 3.5 kg |
| PV-Module (Standard) Weight Dimensions | 3.5 kg 0.63 x 0.43 x 0.03 m |
| PV-Module (Standard) Weight Dimensions Cable | 3.5 kg 0.63 x 0.43 x 0.03 m |
| PV-Module (Standard) Weight Dimensions Cable DC Lamp | 3.5 kg 0.63 x 0.43 x 0.03 m Double coated Radox solar cables 4mm², 6 m 9 W _{DC} energy saving lamp, water resistant, electronic |
| PV-Module (Standard) Weight Dimensions Cable DC Lamp Technology | 3.5 kg 0.63 x 0.43 x 0.03 m Double coated Radox solar cables 4mm², 6 m 9 W _{DC} energy saving lamp, water resistant, electronic ballast integrated in lamp (not bulb) |
| PV-Module (Standard) Weight Dimensions Cable DC Lamp Technology Weight | 3.5 kg 0.63 x 0.43 x 0.03 m Double coated Radox solar cables 4mm², 6 m 9 W _{DC} energy saving lamp, water resistant, electronic ballast integrated in lamp (not bulb) 0.87 kg |
| PV-Module (Standard) Weight Dimensions Cable DC Lamp Technology Weight Dimensions | 3.5 kg 0.63 x 0.43 x 0.03 m Double coated Radox solar cables 4mm², 6 m 9 W _{DC} energy saving lamp, water resistant, electronic ballast integrated in lamp (not bulb) 0.87 kg 0.26 x 0.33 x 0.05 m |
| PV-Module (Standard) Weight Dimensions Cable DC Lamp Technology Weight Dimensions Cable | 3.5 kg 0.63 x 0.43 x 0.03 m Double coated Radox solar cables 4mm², 6 m 9 W _{DC} energy saving lamp, water resistant, electronic ballast integrated in lamp (not bulb) 0.87 kg 0.26 x 0.33 x 0.05 m |
| PV-Module (Standard) Weight Dimensions Cable DC Lamp Technology Weight Dimensions Cable Guarantee | 3.5 kg 0.63 x 0.43 x 0.03 m Double coated Radox solar cables 4mm², 6 m 9 W _{DC} energy saving lamp, water resistant, electronic ballast integrated in lamp (not bulb) 0.87 kg 0.26 x 0.33 x 0.05 m 5 m with cigarette lighter connector |

Paralleling





Accessories



Mounting systems



Inverters



Off-Grid solutions made in Switzerland



SolarBox.ch c/o Solar-Werkstatt Ltd

Alte Obfelderstrasse 68

CH-8910 Affoltern a.A. Switzerland

Tel: +41-44-762 18 18, Fax: +41-44-762 18 15

E-mail: solarbox@solar-werkstatt.ch www.solarbox.ch, www.solar-werkstatt.ch